



NTPT NTK BEARINGS CO.,LTD.

5HR2555TM[F(AP-C),F(AP-CF),F(AP-HC)]+[148-1000/1]LM THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 5HR2555TM[F(AP-C),F(AP-CF),F(AP-HC)]+[148-1000/1]LM

5HR2555TM[F(AP-C),F(AP-CF),F(AP-HC)]+[148-1000/1]LM Bearing 2D drawings and 3D CAD models

| | |
|--|--|
| Days to Ship | 42 Days |
| Rail Width W1 | 22 mm |
| Mounting Height M | 25 mm |
| Number of blocks | 5 |
| Material | Stainless Steel |
| Rail Length L | 148 ~ 1000 mm |
| Accuracy Grade | Standard Grade |
| Callout Size | 2555 |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 25100 |
| Basic Load Rating Static Rating Co(N) | 40800 |
| Allowable static moment MA(N · m) | 1330 |
| Allowable static moment MB(N · m) | 1330 |
| The outside dimension W of block | 33.3 mm |
| The outside dimension L of block | 146.4 mm |
| Mounting Hole Dimension S(M) | M8 |
| The dimension L1 of bocks | 105.4 mm |
| LM Block Surface Treatment (* Surface treatment that differs | Industrial Black Chrome Coating / Industrial Black Chrome Film Treated - |



NTPT NTK BEARINGS CO.,LTD.

| | |
|--|--|
| between the rail and block or only on the rail or block is not available.) | Special Fluororesin Coating / Industrial Hard Chrome Plating |
| LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.) | Not Provided |